

FR20 RACING OIL, 12 X 1 QT/CS



JOE GIBBS RACING
MSDS
PO Box 2607
HUNTERSVILLE NC 28078

**Subject: Material Safety Data
Sheets (497)**

Date: 01/31/2012

Dear Sirs and Madams,

Please find enclosed the MSDS's sent to you in accordance to the regulations of the sending country relative to the products(s).

FR20 RACING OIL, 12 X 1 QT/CS

This information is provided to you for the following reason:

The MSDS has been revised since the product was last ordered by your company.

Thanking you in advance for your cooperation, please accept our best regards,

THE LUBRIZOL CORPORATION
29400 LAKELAND BOULEVARD
WICKLIFFE, OH 44092-2298
PHONE: (440)943-1200
0001 0001537867

Log on to www.mylubrizol.com to get the most up to date MSDS. You can also view the MSDS Change Report online that lists MSDS with changes in the last 30 days.



Prepared according to 29CFR 1910.1200.

1	Chemical Product and Company Identification
----------	--

THE LUBRIZOL CORPORATION
29400 LAKELAND BOULEVARD
WICKLIFFE, OH 44092-2298
PHONE: (440)943-1200

Product Trade Name	FR20 RACING OIL, 12 X 1 QT/CS
CAS Number	Not applicable for mixtures.
Synonyms	None.
Generic Chemical Name	Mixture.
Product Type	Multipurpose.
Preparation/Revision Date	31 January 2012
Transportation Emergency Phone No.	FOR TRANSPORT EMERGENCY call CHEMTREC: (+1) 703-527-3887 (outside the U.S.), 1-800-424-9300 (in the U.S.)
MSDS No.	21415747-1433621-5018271-102103

2	Hazards Identification
----------	-------------------------------

Appearance	Dark amber colored liquid.
Odor	Mild
Principal Hazards	<ul style="list-style-type: none"> This material has no known health hazards.

See Section 11 for complete health hazard information.

3	Composition/Information on Ingredients
----------	---

Hazardous Ingredients	This material has no known hazards under applicable laws.
------------------------------	---

4	First Aid Measures
----------	---------------------------

Eyes	Rinse cautiously with water for 20 minutes or until chemical is removed. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical attention.
Skin	Wash with soap and water. Remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before reuse.
Inhalation	Remove exposed person to fresh air if adverse effects are observed. If irritation persists or if toxic symptoms are observed, get medical attention.
Oral	Do NOT induce vomiting. Never give anything by mouth to a person who is losing consciousness, unconscious or convulsing. Call a poison center or doctor if exposed or you feel unwell.
Additional Information	If exposed or concerned: Get medical attention.

5	Fire Fighting Measures
----------	-------------------------------

Flash Point	242 °C, 467.6 °F COC (Typical)
Extinguishing Media	CO ₂ , dry chemical, foam, water spray, water fog. Water can be used to cool and protect exposed material.
Firefighting Procedures	Recommend wearing self-contained breathing apparatus. Do not use a water jet. Use water to cool containers exposed to fire. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water. Spills produce extremely slippery surfaces. Do not release chemically contaminated water into drains, soil or surface water.
Unusual Fire & Explosion Hazards	Elevated temperatures can lead to the formation of irritating fumes and vapors. Container may rupture in a fire situation. DO NOT USE a solid stream of water. Burning may produce irritating, toxic and obnoxious fumes. See section 10 for additional information.

6	Accidental Release Measures
----------	------------------------------------

Spill Procedures	Only trained personnel should be permitted in area. Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Take precautions to avoid release to the environment. Ventilate area if spilled in confined
-------------------------	--

FR20 RACING OIL, 12 X 1 QT/CS

space or other poorly ventilated areas. Prevent entry into sewers and waterways, dispose of in accordance with all federal, state and local environmental regulation. Material on floors may be slippery. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Place in metal containers for recovery or disposal. Wash spill area with soap and water. Do not touch or walk through spilled material. Pump any free liquid into an appropriate closed container.

7	Handling and Storage
Pumping Temperature	Ambient
Maximum Handling Temperature	70 °C, 158 °F
Handling Procedures	Keep containers closed when not in use. Do not discharge into drains or the environment, dispose to an authorized waste collection point. Use appropriate containment to avoid environmental contamination. When handling, do not eat, drink, or smoke. Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Ground and bond containers when transferring material. Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark or other sources of ignition. Dispose of packaging or containers in accordance with local, regional, national and international regulations.
Maximum Storage Temperature	45 °C, 113 °F
Storage Procedures	Store separately from oxidizers. Take precautions to avoid release to the environment. Store in a dry, well-ventilated place. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store separately from incompatible materials. Keep container tightly closed. Ground all equipment containing material. Do not store in open, unlabeled or mislabeled containers. See section 10 for incompatible materials.
Maximum Loading Temperature	70 °C, 158 °F
8	Exposure Controls/Personal Protection
Exposure Limits	None established
Other Exposure Limits	Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.
Engineering Controls	Material should be handled in enclosed vessels and equipment, in which case general (mechanical) room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air.
Gloves Procedures	Consult clothing/glove manufacturer to determine appropriate type of glove for given situation. Gloves should always be inspected before each use and discarded if they show tears, pinholes, or signs of wear.
Eye Protection	Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.
Respiratory Protection	Use half mask respirator with an organic vapor cartridge if exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.
Clothing Recommendation	Gloves, coveralls, apron, boots as necessary to minimize contact. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. Launder contaminated clothing before reuse.
9	Physical and Chemical Properties
Flash Point	242 °C, 467.6 °F COC (Typical)
Upper Flammable Limit	Not determined.
Lower Flammable Limit	Not determined.
Autoignition Point	Not determined.
Explosion Data	Material does not have explosive properties.
Vapor Pressure	Not determined.
pH	Not determined.
Specific Gravity	0.85 (15.6 °C)
Bulk Density	7.04 Lb/gal, 0.84 Kg/L
Water Solubility	Insoluble.
Percent Solid	Not determined.
Percent Volatile	Not determined.
Volatile Organic Compound	Not determined.
Vapor Density	Not determined.
Evaporation Rate	Not determined.
Odor	Mild
Appearance	Dark amber colored liquid.
Viscosity	613 Centistokes (25 °C) 162 Centistokes (40 °C) 9 Centistokes (100 °C)
Odor Threshold	Not determined.
Boiling Point	Not determined.
Pour Point Temperature	-45 °C, -49 °F
Melting / Freezing Point	Not determined.

The above data are typical values and do not constitute a specification. Vapor pressure data are calculated unless otherwise noted.

FR20 RACING OIL, 12 X 1 QT/CS

10	Stability and Reactivity
Stability	Material is normally stable at room temperature and pressure. See the Handling and Storage Section for further details.
Decomposition Temperature	Not determined.
Incompatibility	Strong oxidizing agents. Nitrates Peroxides. Chlorates
Polymerization	Will not occur.
Thermal Decomposition	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released.
Conditions to Avoid	Do not expose to excessive heat, ignition sources, or oxidizing materials. High temperatures.
11	Toxicological Information
-- ACUTE EXPOSURE --	
Eye Irritation	Not expected to cause eye irritation. Based on data from components or similar materials.
Skin Irritation	Not expected to be a primary skin irritant. Based on data from components or similar materials. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.
Respiratory Irritation	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from similar materials.
Dermal Toxicity	The LD50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials.
Inhalation Toxicity	No data available to indicate product or components may be a toxic inhalation hazard.
Oral Toxicity	The LD50 in rats is > 10,000 mg/Kg. Based on data from components or similar materials. Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in pulmonary edema and chemical pneumonitis.
Dermal Sensitization	No data available to indicate product or components may be a skin sensitizer.
Inhalation Sensitization	No data available to indicate product or components may be respiratory sensitizers.
-- CHRONIC EXPOSURE --	
Chronic Toxicity	No data available to indicate product or components present at greater than 1% are chronic health hazards.
Carcinogenicity	This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Reproductive Toxicity	This product contains para-dodecylphenol. Rats given high, repeated daily doses of para-dodecylphenol by oral intubation experienced adverse reproductive effects. The relevance of these effects to humans is uncertain.
Teratogenicity	This product contains para-dodecylphenol. Pregnant rats given high, repeated daily doses of para-dodecylphenol by oral intubation gave birth to pups with cleft palate and skeletal malformations. The relevance of these effects to humans is uncertain.
-- ADDITIONAL INFORMATION --	
Other	No other health hazards known.
12	Ecological Information
-- ENVIRONMENTAL TOXICITY --	
Freshwater Fish Toxicity	Not determined.
Freshwater Invertebrates Toxicity	The acute EC50 is 10 - 100 mg/L based on component data. Chronic effects expected at 1 - 10 mg/L based on component data.
Algal Inhibition	Not determined.
Saltwater Fish Toxicity	Not determined.
Saltwater Invertebrates Toxicity	Not determined.
Bacteria Toxicity	Not determined.
Miscellaneous Toxicity	Not determined.
-- ENVIRONMENTAL FATE --	
Biodegradation	At least 25% of the components in this product show moderate biodegradation based on OECD 301-type test data
Bioaccumulation	25% or greater of the components potentially bioconcentrate, based on octanol/water coefficients.
Soil Mobility	Not determined.
13	Disposal Considerations
Waste Disposal	This material, if discarded, is not a hazardous waste under RCRA Regulation 40 CFR 261. Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.
14	Transport Information

ICAO/IATA I	Not regulated.
ICAO/IATA II	Not regulated.
IMDG	Not regulated.
IMDG EMS Fire	Not applicable.
IMDG EMS Spill	Not applicable.
IMDG MFAG	Not applicable.
MARPOL Annex II	Not determined.
USCG Compatibility	Not determined.
U.S. DOT Bulk	Not regulated.
DOT NAERG	Not applicable.
U.S. DOT (Intermediate)	Not regulated.
U.S. DOT Intermediate NAERG	Not applicable.
U.S. DOT Non-Bulk	Not regulated.
U.S. DOT Non-Bulk NAERG	Not applicable.
Canada	Not regulated.
Mexico	Not regulated.
Bulk Quantity	85000 KG, 187391 lbs.
Intermediate Quantity	11000 KG, 24251 lbs.
Non-Bulk Quantity	400 KG, 882 lbs.

Review classification requirements before shipping materials at elevated temperatures.

15	Regulatory Information
----	------------------------

-- Global Chemical Inventories --

USA	All components of this material are on the US TSCA Inventory or are exempt.
Other TSCA Reg.	None known.
EU	All components comply with the EU 7th Amendment and are approved for EU sales. Lubrizol must maintain records of all imports of this product into the EU. Third party importers are asked to report every import to The Lubrizol PSCD Manager (Europe), Hazelwood, Derby DE56 1QN, UK.
Japan	All components are in compliance with the Chemical Substances Control Law of Japan.
Australia	This product requires notification before sale in Australia.
New Zealand	May require notification before sale under New Zealand regulations.
Canada	This product requires notification before sale in Canada.
Switzerland	This product requires notification before sale in Switzerland.
Korea	All components are in compliance in Korea.
Philippines	All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).
China	This product requires notification in China.
Taiwan	May require notification before sale in Taiwan.

-- Other U.S. Federal Regulations --

SARA Ext. Haz. Subst.	This product does not contain greater than 1.0% of any chemical substance on the SARA Extremely Hazardous Substances list.								
SARA Section 313	From 0.5 to 1.5 percent zinc compounds; contains 0.1% as Zn.								
SARA 311 Classifications	<table border="1"> <tr> <td>Acute Hazard</td><td>No</td></tr> <tr> <td>Chronic Hazard</td><td>No</td></tr> <tr> <td>Fire Hazard</td><td>No</td></tr> <tr> <td>Reactivity Hazard</td><td>No</td></tr> </table>	Acute Hazard	No	Chronic Hazard	No	Fire Hazard	No	Reactivity Hazard	No
Acute Hazard	No								
Chronic Hazard	No								
Fire Hazard	No								
Reactivity Hazard	No								
CERCLA Hazardous Substances	None known.								

-- State Regulations --

Cal. Prop. 65	This product contains the following chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components: < 0.05 ppm Benzene, CAS no. 71-43-2 < 0.05 ppm cadmium < 0.05 ppm arsenic < 0.05 ppm lead 0.002% Toluene, CAS no. 108-88-3
---------------	--

-- Product Registrations --

U.S. Fuel Registration	Not applicable.
Finnish Registration Number	Not Registered
Swedish Registration Number	Not Registered
Norwegian Registration Number	Not Registered
Danish Registration Number	Not Registered

FR20 RACING OIL, 12 X 1 QT/CS

Swiss Registration Number Not Registered

Italian Registration Number Not Registered

-- Other / International --

Miscellaneous Regulatory Information Not determined.

16	Other Information
-----------	--------------------------

US NFPA Codes

Health	Fire	Reactivity	Special
1	1	1	N/E

(N/E) - None established

HMIS Codes

Health	Fire	Reactivity
0	1	1

Precautionary Labels

- This material has no known health hazards.

Revision Indicators

Section: 15 EU EINECS.

Changed: 31 January 2012

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.