

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 1 of 9

1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT INFORMATION

Product Name: Prestone Extended Life 5/150 Antifreeze Coolant

Product Code: MSDS410

Recommended Use:

Automobile Antifreeze - consumer product.

External Keys:

9985809	Productive Materials
998	Productive Materials
PMRV0862	PMRV
CN36081	GM of Canada Approval Number
12346290	Distributable Material (Part #)
12377912	Distributable Material (Part #)
10-101	Distributable Material (Part #)
10-125	Distributable Material (Part #)
12377963	Distributable Material (Part #)
12378464	Distributable Material (Part #)
21031334	Distributable Material (Part #)
88862642	SPO Catalog Discontinued
DEX-COOL	Primary Tradename - Distributable Material
Antifreeze	
Extended Life	
Coolant	
88862638	Distributable Material (Part #)
88862640	Distributable Material (Part #)
88862645	Distributable Material (Part #)
See HMCS No.	SPO Catalog Discontinued
30002455 for #	
88862642	
12378512	Distributable Material (Part #)

MANUFACTURER INFORMATION

Manufacturer: Honeywell Consumer Products Group

Address:

39 Old Ridgebury Road USA Connecticut 06810-5109 Danbury Mailing

Communication Lines:

Phone	800-862-7737	Information in the U.S.
Phone	800-668-9349	Information in Canada
Phone	800-424-9300	Emergency (CHEMTREC in the U.S.)
Phone	613-996-6666	Emergency (CANUTEC in Canada)
Phone	800-890-2075	Medical Emergencies and all other information (in the U.S)

Comment:

Manufacturer name change. Formerly manufactured by Prestone Products Corporation.

SUPPLIER INFORMATION

Supplier: GM of Canada - Oshawa

Address:

1908 Colonel Sam Drive CAN ON L1H8P7 Oshawa Mailing

2 INGREDIENT INFORMATION

FORMULATION

Ingredients:

Exposure Limits

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 2 of 9

2 INGREDIENT INFORMATION

FORMULATION

Ingredients:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Prefix</u>	<u>Value</u>	<u>Unit</u>	
ETHYLENE GLYCOL	107-21-1	Range	80-95	% Wt	Yes
DIETHYLENE GLYCOL	111-46-6	Range	0 - 5	% Wt	Yes
HEXANOIC ACID, 2-ETHYL-, SODIUM SALT	19766-89-3	Range	1-5	% Wt	No
Neodecanoic acid, sodium salt	31548-27-3	Range	1-5	% Wt	No

3 HAZARDS IDENTIFICATION

Hazards Overview:

EMERGENCY OVERVIEW: Eye and upper respiratory irritant. May cause nausea, vomiting, headache, drowsiness, blurred vision, convulsions, coma or death if ingested or inhaled. Prolonged or repeated skin contact may cause dermatitis or skin sensitization.

Specific Hazards (Routes Of Exposure):

<u>Exposure Routes</u>	<u>Exposure Duration</u>	<u>Observation</u>
Skin Contact	Acute	NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.
Eye Contact	Acute	LIQUID, VAPORS OR MIST MAY CAUSE DISCOMFORT IN THE EYE WITH PERSISTENT CONJUNCTIVITIS, SEEN AS SLIGHT EXCESS REDNESS OR CONJUNCTIVA. SERIOUS CORNEAL INJURY IS NOT ANTICIPATED.
Inhalation	Acute	MAY CAUSE IRRITATION OF THE NOSE AND THROAT WITH HEADACHE, PARTICULARLY FROM MISTS. HIGH VAPOR CONCENTRATIONS CAUSED, FOR EXAMPLE, BY HEATING THE MATERIAL IN AN ENCLOSED AND POORLY VENTILATED WORKPLACE, MAY PRODUCE NAUSEA, VOMITING, HEADACHE, DIZZINESS AND IRREGULAR EYE MOVEMENTS.
Ingestion	Acute	MAY CAUSE ABDOMINAL DISCOMFORT OR PAIN, NAUSEA, VOMITING, DIZZINESS, DROWSINESS, MALAISE, BLURRING OF VISION, IRRITABILITY, BACK PAIN, DECREASE IN URINE OUTPUT, KIDNEY FAILURE, AND CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING IRREGULAR EYE MOVEMENTS, CONVULSIONS AND COMA. CARDIAC FAILURE AND PULMONARY EDEMA MAY DEVELOP. SEVERE KIDNEY DAMAGE WHICH MAY BE FATAL MAY FOLLOW THE SWALLOWING OF ETHYLENE GLYCOL (107-21-1). A FEW REPORTS HAVE BEEN PUBLISHED DESCRIBING THE DEVELOPMENT OF WEAKNESS OF THE FACIAL MUSCLES, DIMINISHING HEARING, AND DIFFICULTY WITH SWALLOWING, DURING THE LATE STAGES OF SEVERE POISONING.

Medical Conditions Aggravated By Exposure:

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 3 of 9

3 HAZARDS IDENTIFICATION

Medical Conditions Aggravated By Exposure:

THE AVAILABLE TOXICOLOGICAL INFORMATION AND A KNOWLEDGE OF THE PHYSICAL AND CHEMICAL PROPERTIES OF THE MATERIAL SUGGEST THAT OVEREXPOSURE IS UNLIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

Additional Health Hazard Data:

CHRONIC EFFECTS: PROLONGED OR REPEATED INHALATION EXPOSURE MAY PRODUCE SIGNS OF CENTRAL NERVOUS SYSTEM INVOLVEMENT, PARTICULARLY DIZZINESS AND JERKING EYE MOVEMENTS. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN SENSITIZATION AND AN ASSOCIATED DERMATITIS IN SOME INDIVIDUALS.

4 FIRST AID MEASURES

First Aid By::

Inhalation REMOVE THE VICTIM TO FRESH AIR. IF BREATHING HAS STOPPED ADMINISTER ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, HAVE MEDICAL PERSONNEL ADMINISTER OXYGEN. GET MEDICAL ATTENTION.

Skin Contact REMOVE CONTAMINATED CLOTHING. IMMEDIATELY WASH CONTACTED AREA THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

Eye Contact IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

Ingestion SEEK IMMEDIATE MEDICAL ATTENTION. IMMEDIATELY CALL LOCAL POISON CONTROL CENTER OR GO TO AN EMERGENCY DEPARTMENT. NEVER GIVE ANYTHING BY MOUTH TO OR INDUCE VOMITING IN AN UNCONSCIOUS OR DROWSY PERSON.

Notes To Physician:

The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning. Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required. There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia. Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required. 4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

5 FIRE FIGHTING MEASURES

Flash Point:

=	254	°F	TOC	(123 °C)
>	230	°F	SETA	(>110 °C)

Explosive Limits:

Upper Explosive Limit (UEL)	Not Determined
Lower Explosive Limit (LEL)	Not Determined

Autoignition Temperature:

Not Determined

Extinguishing Media:

FOR LARGE FIRES, USE ALCOHOL TYPE OR ALL-PURPOSE FOAMS. FOR SMALL FIRES, USE WATER SPRAY, CARBON

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 4 of 9

5 FIRE FIGHTING MEASURES

Extinguishing Media:

DIOXIDE OR DRY CHEMICAL.

Fire and Explosion Hazards:

UNUSUAL FIRE HAZARDS: A SOLID STREAM OF WATER OR FOAM DIRECTED INTO HOT, BURNING LIQUID CAN CAUSE FROTHING.

HAZARDOUS COMBUSTION PRODUCTS: BURNING MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

Special Fire Fighting Procedures:

DO NOT SPRAY POOL FIRES DIRECTLY.

Comment:

FIREFIGHTERS SHOULD WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING FOR FIRES IN AREAS WHERE CHEMICALS ARE USED OR STORED.

6 ACCIDENTAL RELEASE MEASURES

PRECAUTIONS IN CASE OF ACCIDENTAL RELEASE

Personal Precautions:

Wear appropriate protective clothing and equipment.

SPILL OR LEAK PROCEDURES

Recovery:

Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

Disposal:

DISPOSE OF PRODUCT IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

7 HANDLING AND STORAGE

HANDLING

Safe Handling Procedures:

DANGER: Harmful or Fatal if Swallowed

Do not drink antifreeze or solution. Avoid eye and prolonged or repeated skin contact. Avoid breathing vapors or mists. Wash exposed skin thoroughly with soap and water after use. Keep container away from open flames and excessive heat. Do not reuse empty containers unless properly cleaned. Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

NFPA Classification: Not applicable

STORAGE

Storage Conditions:

DO NOT STORE IN OPENED OR UNLABELED CONTAINERS.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

USE GENERAL VENTILATION OR LOCAL EXHAUST AS REQUIRED TO MAINTAIN EXPOSURES BELOW THE OCCUPATIONAL EXPOSURE LIMITS.

EXPOSURE LIMITS

Limit Values:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Type</u>	<u>Value</u>	<u>Specification</u>	<u>Source</u>
ETHYLENE GLYCOL	107-21-1	PEL- Ceiling	50.00ppm	-	OSHA - Permissible Exposure Limits (PELs)
ETHYLENE GLYCOL	107-21-1	GM OEG			GM

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 5 of 9

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS

Limit Values:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Type</u>	<u>Value</u>	<u>Specification</u>	<u>Source</u>
		-Ceiling	50ppm	-	Occupational Exposure Guidelines (OEG)
ETHYLENE GLYCOL	107-21-1	TLV-Ceiling	38.50ppm	-	Threshold Limit Values (TLVs) - ACGIH
ETHYLENE GLYCOL	107-21-1	State-Ceiling	50ppm	-	MICHIGAN
ETHYLENE GLYCOL	107-21-1	State-Ceiling	50ppm	-	NEW YORK
ETHYLENE GLYCOL	107-21-1	State-Ceiling	50ppm	-	TENNESSEE
DIETHYLENE GLYCOL	111-46-6	GM OEG -TWA	155mg/m3	-	GM Occupational Exposure Guidelines (OEG)

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment (PPE):

Eye Protection	SPLASH-PROOF GOGGLES.
Skin Protection	APPROPRIATE PROTECTIVE CLOTHING AS NEEDED TO MINIMIZE SKIN CONTACT.
Respiratory Protection	FOR OPERATIONS WHERE THE TLV IS EXCEEDED A NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES AND DUST/MIST PREFILTERS OR SUPPLIED AIR RESPIRATOR IS RECOMMENDED. EQUIPMENT SELECTION DEPENDS ON CONTAMINANT TYPE AND CONCENTRATION. SELECT AND USE IN ACCORDANCE WITH 29 CFR 1910.134 AND GOOD INDUSTRIAL HYGIENE PRACTICE. FOR FIREFIGHTING, USE SELF-CONTAINED BREATHING APPARATUS.
Hand Protection	CHEMICAL RESISTANT GLOVES SUCH AS NEOPRENE OR PVC WHERE CONTACT IS POSSIBLE.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Color: ORANGE

Odor: CHARACTERISTIC ODOR

Comment:

Physical State: Liquid

PHYSICAL PROPERTIES

pH Value:

Concentrate	Range	8.7	9.2
-------------	-------	-----	-----

Changes of State:

Boiling Point	=	340	°F	(171°C)
Melting/Freezing Point	=	-36	°F	(Melting Point) (-38 °C)

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 6 of 9

9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Vapor Pressure:

Not Determined

Vapor Density:

Not Determined

Evaporation Rate:

Not Determined

Specific Gravity:

Range 1.07 1.14

Solubility:

Water Complete

Viscosity:

Viscosity Not Determined

Total Amount Of:

Percent Volatile Not Determined

Additional Chemical and Physical Data:

Coefficient of Water/Oil Not Determined
Distribution: Determined

Odor threshold

There is no odor threshold data for this product.

10 STABILITY AND REACTIVITY

STABILITY INFORMATION

Stability Under Normal Conditions: Stable

Conditions to Avoid:

None

Incompatible Materials:

Normally unreactive, however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents and materials reactive with hydroxyl compounds.

Hazardous Polymerization:

WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION

Reactions:

Type of Reaction

Reaction Products

Decomposition

DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

11 TOXICOLOGICAL INFORMATION

SCIENTIFIC OBSERVATIONS

LETHAL LIMIT VALUES

Data By Chemical:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Exposure Routes</u>	<u>Type</u>	<u>Prefix</u>	<u>Value</u>	<u>Unit</u>	<u>Species</u>
ETHYLENE GLYCOL	107-21-1	Ingestion	LD50	=	4700	mg/kg	Rat
ETHYLENE GLYCOL	107-21-1	Skin Contact	LD50	=	9530	mg/kg	Rabbit

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 7 of 9

11 TOXICOLOGICAL INFORMATION

SCIENTIFIC OBSERVATIONS

LETHAL LIMIT VALUES

Data By Chemical:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Exposure Routes</u>	<u>Type</u>	<u>Prefix</u>	<u>Value</u>	<u>Unit</u>	<u>Species</u>
DIETHYLENE GLYCOL	111-46-6	Ingestion	LD50	=	12565	mg/kg	Rat
DIETHYLENE GLYCOL	111-46-6	Skin Contact	LD50	=	11890	mg/kg	Rabbit

CLASSIFICATION OF INGREDIENTS

Carcinogenicity:

NONE OF THE COMPONENTS OF THESE PRODUCTS IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY IARC, NTP, ACGIH OR OSHA.

TWO CHRONIC FEEDING STUDIES, USING RATS AND MICE, HAVE NOT PRODUCED ANY EVIDENCE THAT ETHYLENE GLYCOL (107-21-1) CAUSES DOSE-RELATED INCREASES IN TUMOR INCIDENCE OR A DIFFERENT PATTERN OF TUMORS COMPARED WITH UNTREATED CONTROLS. THE ABSENCE OF CARCINOGENIC POTENTIAL FOR ETHYLENE GLYCOL (107-21-1) HAS BEEN SUPPORTED BY NUMEROUS INVITRO GENOTOXICITY STUDIES SHOWING THAT IT DOES NOT PRODUCE MUTAGENIC OR CLASTOGENIC EFFECTS. A CORRELATION HAS BEEN ESTABLISHED BETWEEN MUTAGENIC ACTIVITY AND CARCINOGENIC ACTIVITY FOR MANY CHEMICALS. TOLYTRIAZOLE HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC, ACGIH OR OSHA.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

Mutagenicity:

THIS PRODUCT CONTAINS LESS THAN 0.5% TOLYTRIAZOLE WHICH HAS DEMONSTRATED MUTAGENIC ACTIVITY IN A BACTERIAL TEST SYSTEM. A CORRELATION HAS BEEN ESTABLISHED BETWEEN MUTAGENIC ACTIVITY AND CARCINOGENIC ACTIVITY FOR MANY CHEMICALS.

Reproductive Effects:

CHRONIC EFFECTS: ETHYLENE GLYCOL (107-21-1) HAS BEEN FOUND TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. THE SIGNIFICANCE OF THIS FINDING TO HUMANS HAS NOT BEEN DETERMINED. Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1000 and 2500 mg/m³ for six hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1000 and 2500 mg/m³) and developmental no-effects concentration (based on maternal toxicity) was 500 mg/m³. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause reproductive harm. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Comment:

Prod.Name: Prestone Extended Life 5/150 Antifreeze
Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 8 of 9

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Comment:

ETHYLENE GLYCOL (107-21-1) LC50 GOLDFISH: 5,000 MG/L/24 HR. AT 20C STATIC CONDITIONS. TOXICITY THRESHOLD (CELL MULTIPLICATION INHIBITION TEST): BACTERIAL (PSEUDOMONAS PUTIDA): 10,000 MG/L. PROTOZOA (ENTOSIPHON SULCATUM AND URONEMA PARDUCZI CHATTON-LWOFF): >10,000 MG/L. ALGAE (MICROCYSTIS AERUGINOSA): 2,000 MG/L. GREEN ALGAE (SCENEDESMUS QUANDRICAUDA): >10,000 MG/L.

13 DISPOSAL CONSIDERATIONS

Waste Disposal Information:

DISPOSE OF PRODUCT IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

14 TRANSPORT INFORMATION

DOT Information:

U.S. DOT HAZARD CLASSIFICATION: Not Regulated (unless package contains a reportable quantity)
DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

DOT Shipping Name:

RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

DOT Hazard Class:

9

DOT UN Code:

UN3082

DOT Packing Group:

III

Comment:

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (8,333 LBS/933 GAL.) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:
IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

15 REGULATORY INFORMATION

LABELLING

Hazard Codes:

NFPA Flammability 1
NFPA Health 2
NFPA Reactivity 0

Comment:

NFPA CLASSIFICATION: Not applicable.

NATIONAL REGULATIONS

SARA 311/312: Yes

SARA 313: Yes

Immediate Health: Yes

Delayed Health: Yes

Fire: No

Sudden Pressure Release: No

Reactive: No

Other Regulation:

EPA SARA 313:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO ANNUAL RELEASE REPORTING REQUIREMENTS UNDER SARA TITLE III, SECTION 313 (40 CFR 372): ETHYLENE

Prod.Name: Prestone Extended Life 5/150 Antifreeze Coolant
Manufacturer: Honeywell Consumer Products Group
Supplier: GM of Canada - Oshawa
HMCS ID: 339416
SUC: 04 - Metal Working Fluids and Lubricants

MATERIAL SAFETY DATA SHEET

Revision: 19.Aug.2010
Effective: 19.Aug.2010
Print Date: 16.Aug.2011
Page: 9 of 9

15 REGULATORY INFORMATION

NATIONAL REGULATIONS

Other Regulation:

PROTECTION OF STRATOSPHERIC OZONE:

CERCLA SECTION 103:

EPA TSCA INVENTORY:

GLYCOL (107-21-1): 85-95%.
THIS PRODUCT IS NOT KNOWN TO CONTAIN OR TO HAVE BEEN MANUFACTURED WITH OZONE DEPLETING SUBSTANCES AS DEFINED IN 40 CFR PART 82, APPENDIX A TO SUBPART A. SPILLS OF THIS PRODUCT OVER THE RQ (REPORTABLE QUANTITY) MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. THE RQ FOR THIS PRODUCT, BASED ON THE RQ FOR ETHYLENE GLYCOL (107-21-1) (95% MAXIMUM) OF 5,000 LBS IS 5,260 LBS. MANY STATES HAVE MORE STRINGENT RELEASE REPORTING REQUIREMENTS. REPORT SPILLS REQUIRED UNDER FEDERAL, STATE AND LOCAL REGULATIONS.
ALL OF THE COMPONENTS OF THIS MATERIAL ARE LISTED ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) CHEMICAL SUBSTANCES INVENTORY.

STATE/LOCAL REGULATIONS

Comment:

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause cancer and/or reproductive harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

16 OTHER INFORMATION

Comments:

Additional Exposure Limits: GM Occupational Exposure Guidelines (OEG) and State-TWA's were provided by General Motors.